AUTOMOTIVE · PASSENGER CAR ENGINE OILS

SYNMAX STELLAR 5W-30.

Full synthetic mid-SAPS engine oil formulated with advanced performance technology for the latest designs of petrol and diesel engine.

APPLICATION

- Stellantis group petrol and diesel engines
- Mercedes-Benz long-life servicing
- Mixed European car fleets

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ACEA	C2, C3
API	SN, SM, SL
GM	dexos2™
MB	229.52, 229.51, 229.31
PSA	B71 2297, B71 2290
Stellantis	FPW 9.55535.03

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 5W-30**
Base Oil		**Full synthetic**
Specific Gravity @ 15.6°C		**0.846**
Kinematic Viscosity @ 100°C	cSt	**11.8**
Viscosity Index ASTM D2270		**183**
Sulphated Ash ASTM D874		**0.8 % max**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963