COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

SYNMAX TRITON XFE 5W-20.

A full synthetic, low SAPS 5W-20 heavy duty diesel oil for the very newest Scania and MAN engines, approved to Scania LDF-5 and MAN M3977.

0.856	-42 °C	Green
Density @ 15	Pour point	Colour

APPLICATION

- Latest Scania engines on LDF-5
- MAN M3977 applications
- Fuel economy programmes on modern fleets
- Long-haul operations with aftertreatment

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

SCANIA	LDF-5
MAN	M3977

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour ASTM D1500		**Green**
KV @ 100°C	cSt	**8.4**
KV @ 40°C	cSt	**49.2**
Viscosity Index ASTM D2270		**146**
Density @ 15°C ASTM D4052		**0.856**
Pour Point ASTM D97	°C	**-42**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963