INDUSTRIAL OILS · COMPRESSOR OILS

# SYNTH PAO COMPRESSOR OIL 32.

The lightest grade in the full synthetic compressor range, and the one to reach for when cold starting is the constraint.

| 32 cSt | 0.84 | 210 °C | -55 °C |
|---|---|---|---|
| Viscosity @ 40°C | Relative Density @ 15 | Flash point | Pour point |

## APPLICATION

- Cold-start critical compressor installations
- Light-duty rotary screw machines
- Outdoor and unheated compressor housings

### NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **DIN** | 51506 (VDL) |
| **ISO** | DP 6521 (DAG) |

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Relative Density @ 15°C | | **0.84** |
| Pour Point | °C | **-55** |
| Flash Point, COC °C min | | **210** |
| Viscosity, cSt @ 40°C | | **32** |
| Rust (ASTM D 665 A) | | **Pass** |

Typical values, not a specification.

### PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963