GREASES · HIGH TEMPERATURE GREASES

SYNTHETIC HIGH TEMP 2.

A synthetic high temperature grease on a lithium complex thickener with PTFE.

APPLICATION

- Oven, dryer and stenter bearings
- Kiln car and furnace trolley bearings
- Hot process plant running continuously
- Bearings cycling between cold start and high heat

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth Brown Grease**
Thickener		**Lithium Complex**
NLGI Classification		**2**
Base Oil		**Synthetic Hydrocarbon**
Solid Lubricant		**PTFE**
Dropping Point (ASTM D2265)	°C	**> 250**
Dynamic Corrosion Resistance (EMCOR) (IP 220)		**0 : 0**
Weld Load (Shell 4 Ball)		**355 Kgs**
Load Wear Index		**68 Kgs**
Corrosion (ASTM D130)		**1b**
dN Factor		**750,000**
Operating Temperature Range	°C	**-50°C to +220**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963