GREASES · HIGH TEMPERATURE GREASES

SYNTHETIC HIGH TEMP RED 007 GREASE.

The semi-fluid member of the synthetic high temperature family: an NLGI 00 lithium complex grease on a 460 cSt synthetic blend with PTFE.

APPLICATION

- Centralised lubrication of hot bearings
- Semi-fluid feed to oven and dryer bearings
- Hot gearboxes designed for a slumping grease

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth Red grease**
Thickener		**Lithium Complex**
NLGI classification		**00**
Base oil		**A blend of synthetic oils**
Base oil Viscosity	cSt	**460**
Solid lubricant		**PTFE**
Dropping point (ASTM D2265)	°C	**>230**
Dynamic corrosion resistance (EMCOR) (IP 220)		**0:0**
Weld Load (Shell 4 Ball IP 239/ASTM D2596)		**355kgs**
Load Wear Index		**68kg**
Corrosion (ASTM D130)		**1b**
dN factor		**750,000**
Operating temperature range	°C	**-50°C to 170°C with short periods up to 200**

Typical values, not a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963