COMMERCIAL VEHICLES · TRANSMISSION & AXLE OILS

TECHGEAR S 75W80.

A fully synthetic, fuel-efficient gear oil for commercial vehicle drivelines, formulated for rapid circulation from cold start and extended service life under heavy-duty operating conditions.

56.7 cSt	9.61 cSt	0.853	192 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Axles, transfer cases and final drives on late-model trucks and buses
- Non-synchronised manual transmissions requiring API MT-1

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 15.6°C		**0.853**
Viscosity @ 40°C	cSt	**56.7**
Viscosity @ 100°C ASTM D445	cSt	**9.61**
Flash Point ASTM D92	°C	**192**
Pour Point ASTM D97	°C	**-42**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4/5, MT-1
MIL-PRF	2105E
SAE	J-2360
Arvin	Meritor 076
SDAF	requirement
MAN	342 Type S1

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963