INDUSTRIAL OILS · COMPRESSOR OILS

TITANIUM V COMPRESSOR OIL 100.

A semi-synthetic compressor oil that sits deliberately between the mineral and full synthetic ranges.

100 cSt	0.88	210 °C	-30 °C
Viscosity @ 40°C	Relative Density @ 15°C / 4	Flash point	Pour point

APPLICATION

- Workshop and light industrial compressors
- 4,000 hour extended service intervals
- Operators stepping up from a mineral fill without paying for full synthetic

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ISO	6743-3:2003 L-DAH specification, DP 6521 (DAG)
DIN	51506 (VDL)

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Relative Density @ 15°C / 4°C		**0.88**
Pour Point	°C	**-30**
Flash Point, COC °C min		**210**
Viscosity, cSt @ 40°C		**100**
Rust (ASTM D 665 A)		**Pass**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963