COMMERCIAL VEHICLES · TRANSMISSION & AXLE OILS

TRANSPLUS Z 75W-80.

A full synthetic 75W-80 manual transmission fluid for modern commercial vehicle gearboxes, including automated manuals.

57.0 cSt	9.5 cSt	0.848	-43 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Pour point

APPLICATION

- Volvo I-Shift and automated manual gearboxes
- MAN and DAF manual transmissions
- Eaton extended drain applications
- Modern synchromesh heavy vehicle gearboxes

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4 / GL-4S
ZF	TE-ML 02L
MAN	341 Type E3, Z4
VOLVO	97305, 97307 (i-Shift requirement)
EATON	extended drain
DAF	requirement

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity @ 100°C	cSt	**9.5**
Viscosity @ 40°C	cSt	**57.0**
Viscosity Index ASTM D2270		**150**
Density @ 15.6°C		**0.848**
Pour Point	°C	**-43**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963