MASTER FLUID SOLUTIONS · SOLUBLE CUTTING FLUIDS

TRIM E950.

High-performance, aerospace-approved metalworking fluid compliant with Rolls-Royce CSS129 and CSS131, developed for demanding precision machining.

APPLICATION

- Aerospace and defence precision machining
- Titanium, nickel-based superalloys and aluminium alloys
- Sites needing extended sump life and fewer cleanouts

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Rolls-Royce	CSS129, CSS131
Aerospace	approved

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Type		**Soluble oil emulsion**
Typical Dilution	%	**5 – 10**
Lubricity		**High**
Chlorine ASTM D808		**None**

Typical values, not a specification.

PACK SIZES

205 L, 1000 L IBC, Bulk. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963