MASTER FLUID SOLUTIONS · SOLUBLE CUTTING FLUIDS

TRIM MicroSol 585XT.

High-lubricity semi-synthetic micro-emulsion metalworking fluid delivering extended sump life and excellent foam control against earlier generation semi-synthetics.

APPLICATION

- Titanium and high-nickel alloy machining
- Aerospace aluminium and exotic alloys
- Grinding, turning, drilling, tapping and milling
- Heavy-duty roughing and long cycle-time operations

BENEFITS

- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Rolls-Royce	CSS 127, Nuclear Class A – A17929
Airbus	80-T-30-4010
Boeing	BAC5008
Safran	PCS-4001 / 4002 / PR6300 Index A
Pratt	& Whitney PMC 9362
Bombardier	BAMS 569-001
GE	Aviation SDS# EVEN-11232
Lockheed	Martin G34.62 / G74.0051 / F74.0051
Aerojet	ASTM F 945
Applied	Materials UHV
Lord	Corporation MTL-S-0136

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Type		**Semi-synthetic micro-emulsion**
Light Duty	%	**4.0 – 6.5**
Moderate Duty	%	**6.5 – 8.5**
Heavy Duty	%	**8.5 – 10.0**
Chlorine ASTM D808		**None**
Formaldehyde Releasers		**None**
Nitrites / Phenols		**None**

Typical values, not a specification.

PACK SIZES

205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963