AUTOMOTIVE · PASSENGER CAR ENGINE OILS

TURBOLUBE HD 10W-40.

Semi-synthetic engine oil suitable for many cars and light commercial vehicles with either turbocharged or normally-aspirated engines.

89.9 cSt	13.6 cSt	0.867	205 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Older passenger cars
- Light commercial vehicles
- Turbocharged and naturally aspirated engines

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	SG/CF-4

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 10W-40**
Base Oil		**Semi-synthetic**
Specific Gravity @ 15.6°C		**0.867**
Kinematic Viscosity @ 40°C	cSt	**89.9**
Kinematic Viscosity @ 100°C	cSt	**13.6**
Viscosity Index ASTM D2270		**152**
Flash Point (COC)	°C	**205**
Pour Point ASTM D97	°C	**-30**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963