GREASES · HIGH TEMPERATURE GREASES

# ULTRA HIGH TEMPERATURE GREASE.

The extreme end of the range: a graphite dispersion in polyalkylene glycol for service up to 600 °C.

| 128 cSt | 25 cSt | Nil | 2 |
|---|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Dropping point | NLGI grade |

## APPLICATION

- Furnace door and charging gear
- Kiln car bearings and running gear
- Heat treatment plant
- Anywhere above the limit of every other grease

### NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

## BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Colour<br>ASTM D1500 | | **Black** |
| Base Oil | | **Polyalkaline glycol** |
| NLGI Classification | | **2** |
| Dropping Point (ASTM D2265) | | **Nil** |
| Micronised Graphite Content | % | **15** |
| Base Fluid Viscosity (IP71) @ 40°C | cSt | **128** |
| Base Fluid Viscosity (IP71) @ 100°C | cSt | **25** |
| Operating Temperature Range<br>dry film | °C | **-30°C to +200°C (grease film); 200°C to 600** |

Typical values, not a specification.

### PACK SIZES

12.5 kg, 50 kg, 180 kg

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963