TEXTILE LUBRICANTS · FIBRE & YARN LUBRICANTS

UNILUBE WWA.

UNILUBE WWA is an aqueous solution of synthetic water-soluble lubricants formulated for application as a yarn dressing at beaming off after warping or at re-beaming.

APPLICATION

- Yarn dressing at beaming off / re-beaming - Woollen Yarn 2.0-6.0%
- Worsted Yarn 2.0-4.0%
- Synthetic/Wool Blend 1.6-4.0%
- Synthetic/Cotton Blend 0.8-3.6%
- Synthetic Staple 0.8-3.6%
- Synthetic Filament 0.6-1.6%
- Linen & Linen Blends 3.9-4.0%

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Water-white viscous liquid**
% Activity	%	**25 ± 1**
pH		**6.0-8.0**
Ionic Character		**Nonionic**
Viscosity (B4 Ford Cup)	°C	**< 20 secs @ 20**
Anti-static Properties		**Excellent**
Solubility	°C	**Soluble in water and dry cleaning solvents at 50-100**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963