SPECIALITIES · ANTIFREEZE & COOLANTS

UNIVERSAL ANTIFREEZE 50:50.

The conventional blue coolant supplied ready mixed at 50:50, giving frost protection to -40 °C straight from the drum.

APPLICATION

- Workshop servicing where mix accuracy matters
- Roadside and field top-ups
- Hard water areas where dilution would scale the system
- Fleet operations standardising on one product

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Blue**
Conforms to British Standard		**BS 6580:2010**
Freeze Point Protection	°C	**-40**
Specific Gravity ASTM D1298		**1.06-1.075**
pH Value 50% Aqueous Solution		**7.8**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963