INDUSTRIAL OILS · VACUUM & AIRLINE OILS

# VACUUM PUMP OIL 100.

A mineral vacuum pump oil for rotary and slide vane pumps.

| 11.5 cSt | >225 °C | -18 °C |
|---|---|---|
| Viscosity @ 100°C | Flash point | Pour point |

## APPLICATION

- Rotary vane and slide vane vacuum pumps
- Vacuum packing and forming lines
- Laboratory and process vacuum systems
- Vacuum lifting and handling equipment

### NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Kinematic Viscosity (cSt) @ 40°C | | **90.0 – 110.0** |
| Kinematic Viscosity (cSt) @ 100°C | | **11.5** |
| Viscosity Index<br>ASTM D2270 | | **102** |
| Density @ 15.6°C | | **0.880 – 0.900** |
| Flash Point (COC) | °C | **>225** |
| Pour Point | °C | **-18** |
| Vapour Pressure kPa @ 20°C | | **<0.1** |

Typical values, not a specification.

### PACK SIZES

5 L, 20 L, 205 L

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963