METALWORKING FLUIDS · DRAWING & FORMING OILS

VANISHING OIL S25.

VANISHING OIL S25 is a low viscosity lubricant designed for high speed presswork operations producing relatively small or flat components, formulated with a high level of natural ester for high film strength, excellent s

2 mm2/s cSt	0.812	75 °C
Viscosity @ 40°C	Specific Gravity @20	Flash point

APPLICATION

- Drawing
- Stamping and blanking
- Light to moderate draws
- High speed operations
- Light to medium gauge sheet

NOT RECOMMENDED

- × **Machining of magnesium, or of aluminium where a low-pH fluid is required**
- × **Use as a hydraulic or slideway oil - cross-contamination will shorten sump life**

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind - free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour ASTM D1500		**Light yellow**
Viscosity @40°C		**2 mm2/s**
Chlorine ASTM D808		**No**
Sulphur		**No**
Ester		**Yes**
Flash Point	°C	**75**
Specific Gravity @20°C		**0.812**

Typical values, not a specification.

PACK SIZES

25 L / 205 L / 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963