GREASES · AUTOMOTIVE GREASES

WHITE BRAKE GREASE.

A calcium 12-hydroxystearate grease with 5% zinc oxide, for brake hardware.

APPLICATION

- Brake slider pins and caliper hardware
- Backing plate contact points
- Preventing seized brake components
- General corrosion protection on chassis fittings

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Off-white smooth grease**
NLGI classification		**2**
Base Oil		**Highly refined mineral oil**
Thickener		**Calcium 12 hydroxy stearate**
Zinc oxide content	%	**5**
Operating temperature range	°C	**-20°C to +110**
Water washout @38°C (ASTM D1264)	%	**2**
Water washout @79°C (ASTM D1264)	%	**5**
Dropping point (IP132)		**+140°C min**

Typical values, not a specification.

PACK SIZES

500 g, 3 kg, 12.5 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963