GREASES · LITHIUM COMPLEX GREASES

WTL 2 GREASE.

A lithium complex grease.

450 cSt	250 max °C	2
Viscosity @ 40°C	Dropping point	NLGI grade

APPLICATION

- Slow, heavily loaded bearings
- Wide operating temperature range applications
- Industrial and automotive general use

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Brown smooth grease**
NLGI classification		**2**
Thickener		**Lithium complex**
Base Oil viscosity @40°C (IP71)	cSt	**450**
Copper corrosion (IP112)		**Pass**
Water washout @38°C (IP215)	%	**3**
Resistance to corrosion EMCOR (IP220)		**0 : 0**
Four Ball Weld Load (IP239)		**315kgs**
Wear Load Index		**62**
Timken OK Load (IP326)		**20kgs**
Dropping point (IP1322)		**250°C max**
Operating temperature range	°C	**-20°C to + 150**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963