SPECIALITIES · ANTIFREEZE & COOLANTS

X-OAT LONGLIFE VCS-2 ANTIFREEZE.

A premium MEG-based extended life coolant using the latest OAT chemistry, free from 2-EHA, nitrites and borates.

APPLICATION

- Systems specifying 2-EHA free coolant
- Volvo, Mack and Renault VCS-2 requirements
- Jaguar Land Rover STJLR.03.5212
- Extended-life fills in mixed fleets

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 16 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Pink/Light Red Colour**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010
ASTM	D6210, D3306
SAE	J1034
AFNOR	R15-601
JIS	K2234-2018
	CATERPILLAR/PERKINS, CLAAS, DAF, VOITH
ISUZU/UD	TRUCKS
JOHN	DEERE POWER SYSTEMS
JAGUAR	ST JLRL.03.5212
LAND	ROVER ST JLRL.03.5212
MACK	VCS-2
RENAULT	VCS-2
VOLVO	VCS-2

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963