FOOD GRADE

SARFOOD PAO SPIRAL FREEZER OIL 22.

A food grade fluid built for one of the most awkward duties in food manufacturing: the gearbox on a spiral freezer.

APPLICATION

- Spiral freezer gearboxes
- Blast freezer and cold store drives
- Low temperature hydraulic systems
- Chilled and frozen food production lines

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

All	ingredients are FDA listed, grades contain no genetically-modified ingredients, and do not contain any nut oil or derivatives
Meets	the requirements of NSF and InS H1 Guidelines, the USDA 1998 H1 Guidelines

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear fluid**
Viscosity @ 40 °C	cSt	**22**
Temperature Range	°C	**-65 to +120**
Flash Point (ISO 2592)	°C	**>200**
FZG Load Stage		**11 Pass**

Typical values, not a specification.

PACK SIZES

5 L / 20 L / 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963