FOOD GRADE · FOOD GRADE GREASES

SARFOOD PREMIER EP2 GREASE.

A food grade calcium sulphonate grease on PAO base oil - the premium chemistry in the range.

APPLICATION

- Pellet press machines
- Low to medium speed bearings under heavy load
- Hot and wet processing areas
- Bearings on infrequent relubrication intervals

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

FDA	listed ingredients
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
Water	Regulations Advisory Scheme (WRAS) approval
No	genetically-modified ingredients, nut oil or derivatives

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963

FOOD GRADE · FOOD GRADE GREASES · CONTINUED

SARFOOD PREMIER EP2 GREASE.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth beige grease**
NLGI Classification		**No. 2**
Thickener		**Calcium Sulphonate**
Base Oil		**High viscosity PAO**
Rust Test (ASTM D1743)		**Pass**
Copper Corrosion (ASTM D4048)		**1B**
Drop Point (IP 132)	°C	**>270**
Water Washout (ASTM D1264) @ 80°C		**3.5% max.**
Timken OK Load (ASTM D2509)		**27.2 kg**
Shell Four Ball (IP239)		**Weld Load: 500 kg**
Shell Four Ball (IP239)		**Mean Hertz Load: 55 kg**
Operating Temperature Range	°C	**-40°C to +170°C; Short periods to 220**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.