FOOD GRADE · FOOD GRADE MULTI-PURPOSE OILS

SARFOOD PTFE MULTILUBE 32.

The food grade equivalent of the can of maintenance oil that lives in every workshop - a light PTFE-fortified multi-purpose lubricant with penetrating and dewatering properties.

APPLICATION

- General maintenance lubrication after washdown
- Displacing water from hinges and slides
- Freeing and penetrating in production areas
- Light lubrication of conveyors and guides

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

All	ingredients are FDA listed under 21 CFR 178.3570

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Pale coloured liquid**
Base Oil Type		**Synthetic fluid**
Viscosity at 40 °C	cSt	**26-32**
Solid lubricant		**PTFE**
Operating Temperature Range	°C	**-50 °C to +180**
Copper corrosion test – (IP 112)(ASTM D130)		**1b**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963