FOOD GRADE · FOOD GRADE GREASES

SARFOOD STANDARD GREASE.

The workhorse food grade grease: a calcium 12-hydroxystearate soap on technical white oil, built for plant that gets washed down.

APPLICATION

- General bearing greasing on food plant
- Areas subject to frequent washdown
- Plain and anti-friction bearings
- Conveyors, mixers and packaging machinery

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

FDA	listed ingredients
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients, nut oil or derivatives

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

FOOD GRADE · FOOD GRADE GREASES · CONTINUED

SARFOOD STANDARD GREASE.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth Adhesive Grease**
Colour ASTM D1500		**Off White**
NLGI Classification		**2**
Thickener		**Calcium 12 Hydroxy Stearate**
Base Oil		**Technical White Oil**
Water Washout (IP215) @ 38°C	%	**4**
Water Washout (IP215) @ 79°C	%	**8**
Dropping Point (IP132)		**140°C min**
Copper Corrosion (IP112)		**Pass**
Oil Separation (IP121) 7 days @ 40°C		**4% max**
Resistance To Corrosion EMCOR (IP220)		**0 : 0**
Four Ball Weld Load (IP239)		**315**
Scar Diameter For 1 Hr @ 40 kg	mm	**0.56**
Operating Temperature Range	°C	**-20°C to 110**
Worked Penetration (IP50)		**265 to 295**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.