INDUSTRIAL OILS · MOULD RELEASE AGENTS

SARFORM 327.

A very low viscosity chemical release agent developed for modern brick and concrete manufacture, and particularly effective on refractory and kiln brick mouldings.

1.92 cSt	0.814	70-80 °C
Viscosity @ 40°C	Specific Gravity @ 15	Flash point

APPLICATION

- Refractory and kiln brick moulding
- High-volume brick production
- Fine-detail mould faces

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Thin, pale liquid**
Specific Gravity @ 15°C		**0.814**
Viscosity @ 40°C	cSt	**1.92**
Flashpoint	°C	**70-80**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963