INDUSTRIAL OILS · MOULD RELEASE AGENTS

SARFORM LF MEDIUM.

The medium viscosity grade of the low odour range, for moulds that need a slightly heavier film than the LIGHT grade will leave - vertical faces, deeper profiles, or moulds standing between treatment and pour.

6 – 8 cSt	0.871	> 150 °C
Viscosity @ 40°C	Specific Gravity @ 20	Flash point

APPLICATION

- Vertical and deep-profile moulds
- Enclosed production with heavier film requirement
- Moulds standing before pour

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Low Viscosity, Pale Amber Liquid**
Odour		**Low**
Specific Gravity @ 20°C		**0.871**
Viscosity @ 40°C	cSt	**6 – 8**
Flashpoint	°C	**> 150**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963