INDUSTRIAL OILS · INDUSTRIAL GEAR OILS

SARGEAR 460 EP.

A sulphur-phosphorus EP industrial gear oil on solvent-refined mineral base stocks, built for enclosed gearboxes carrying real load.

APPLICATION

- Worm drives and heavily loaded reducers
- Hot-running gearboxes needing more film
- Applications specifying DIN 51517 Part 3 CLP

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51517 Part 3 (CLP)
ISO	12925-1 (CKC)
	GB5903-2011 (CKC)
JIS	K 2219:2006 (Class 2)
David	Brown S1.53.101(E)
AGMA	9005-E02
AIST	(US Steel) 229

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity @ 40 °C		**460**
Density @ 15 °C ASTM D4052		**0.898**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963