INDUSTRIAL OILS · INDUSTRIAL GEAR OILS

SARGEAR SYNTH PAG 460.

A 100% synthetic polyalkylene glycol EP gear oil, and a genuinely different animal from a mineral or PAO gear oil.

64 cSt	1.007	> 225 °C	–28 °C
Viscosity @ 100 °C	Density @ 20 °C, kg/m³	Flash point	Pour point

APPLICATION

- Worm gearboxes, where the efficiency gain is largest
- Hot-running drives at the limit of a mineral oil
- Energy reduction projects on gear-driven plant
- Gearboxes specified for a PAG fill by the builder

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51517 Part 3 (CLP)
David	Brown Type G

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 20 °C	kg/m³	**1.007**
Viscosity @ 100 °C	mm²/s	**64**
Flash Point	°C	**> 225**
Pour Point	°C	**–28**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963