INDUSTRIAL OILS · INDUSTRIAL GEAR OILS

# SARGEAR SYNTH PAO 68.

A full synthetic Group IV polyalphaolefin gear and bearing oil for severe duty.

| 68 cSt | 210 °C | -43 °C | Clear |
|---|---|---|---|
| Viscosity @ 40°C | Flash point | Pour point | Appearance |

## APPLICATION

- Wind turbine gearboxes and bearings
- Outdoor drives with a wide temperature swing
- Extended-drain industrial gearing
- Hot, heavily loaded reducers

### NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **DIN** | 51517 Part 3 |
| **AGMA** | 9005-E02 (EP) |

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

INDUSTRIAL OILS · INDUSTRIAL GEAR OILS · CONTINUED

# SARGEAR SYNTH PAO 68.

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Clear** |
| Kinematic Viscosity @ 40°C | | **68** |
| Viscosity Index (ASTM D2270) | | **135** |
| Pour Point | °C | **-43** |
| Flash Point, (COC) | °C | **210** |
| Foaming (ASTM D892) – After sequence 1 | | **Nil** |
| Foaming (ASTM D892) – After sequence 2 | | **Nil** |
| Copper Corrosion<br>ASTM D130 | | **1b** |
| Biodegradability % (ISO 9439) | | **>60** |
| FZG Gear Test Stage | | **12** |

Typical values, not a specification.

**PACK SIZES**

5 L, 20 L, 205 L

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963