GREASES · CALCIUM & CALCIUM SULPHONATE GREASES

# SARGREASE CBS 2.

A calcium sulphonate complex grease - the premium water-resistant chemistry, and one of the few greases where the thickener itself carries load.

| 220 cSt | >280 °C | No.2 |
|---|---|---|
| Viscosity @ 40°C | Dropping point | NLGI grade |

## APPLICATION

- Steel mill and continuous casting bearings
- Marine deck machinery
- Extended lubrication intervals in wet, hot service
- Paper machine wet end bearings

### NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

## BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Smooth, beige grease** |
| Thickener | | **Calcium Sulphonate Complex** |
| NLGI Classification | | **No.2** |
| Base Oil Viscosity@40°C (IP71) | cSt | **220** |
| Water Washout (IP215, ASTM D1264) | % | **<1** |
| Dropping Point (ASTM D1264) | °C | **>280** |
| Operating temperature range | °C | **-30°C to +150°C, occasional peak to 220** |

Typical values, not a specification.

### PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963