GREASES · CALCIUM & CALCIUM SULPHONATE GREASES

SARGREASE CGR2.

A calcium-thickened grease.

140 min °C	2	Black
Dropping point	NLGI grade	Colour

APPLICATION

- Worn plain bearings and slides
- Marine and humid industrial applications
- Extending the life of worn components
- Heavy slow-moving surfaces

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth grease**
Colour ASTM D1500		**Black**
NLGI Classification		**2**
Base Oil		**Highly refined mineral oil**
Base Oil viscosity @ 38°C	cSt	**110**
Thickener		**Calcium hydroxystearate**
Copper Corrosion (IP112)		**Pass**
Dropping Point (IP132)		**140°C min**
Resistance to Corrosion (Emcor IP220)		**0:0**
Water Washout (ASTM D1264) @ 38°C	%	**3**
Four Ball Weld Load (IP239) kg		**315**
Worked penetration (IP50)		**265 to 295**
Operating Temperature Range	°C	**-20°C to +110**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963