GREASES · LITHIUM-CALCIUM GREASES

SARGREASE LC2.

A mixed lithium-calcium soap grease, which is a deliberate compromise and a good one: lithium brings mechanical stability and temperature capability, calcium brings water resistance, and the mixed soap gets a useful shar

APPLICATION

- Bearings exposed to water washout or ingress
- General plant in wet conditions
- Mixed metal assemblies

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth grease**
Colour ASTM D1500		**Light Brown**
NLGI Classification		**2**
Thickener		**Lithium-Calcium**
Copper Corrosion (IP112)		**Negative**
Aluminium Corrosion (mod IP112)		**Negative**
Mild Steel Corrosion (mod IP112)		**Negative**
Dropping Point (ASTM D566)		**160°C min**
Water Washout (IP215) @ 38°C	%	**2**
Water Washout (IP215) @ 79°C	%	**3**
Four Ball Weld Load (IP239)		**285kg**
Timken OK Load (IP326) 45lbs		**20kg**
Operating Temperature Range	°C	**-25°C to +140**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963