GREASES · HIGH TEMPERATURE GREASES

SARGREASE PB 30M.

A hydrocarbon polymer liquid grease for very high temperature, slow speed bearings - the 180 °C to 300 °C range where every conventional grease has already failed.

APPLICATION

- Kiln and oven conveyor bearings
- Slow speed bearings above 180 °C
- Furnace trolley and roller bearings
- Where conventional greases carbonise and jam

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

NSF	H2

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Viscous liquid grease**
Colour ASTM D1500		**Grey/black**
Base Oil Type		**Hydrocarbon polymer**
Copper (IP112)		**Negative**
Mild Steel (IP112)		**Negative**
Four Ball Weld Load (IP239)		**178kg**
Operating Temperature Range	°C	**180°C to 300**

Typical values, not a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963