INDUSTRIAL OILS · GENERAL PURPOSE OILS

SARLUBE OIL 150.

A straight, solvent-refined mineral machine oil with no EP or anti-wear package - and that simplicity is the point.

135 – 165 cSt	0.891	223 °C	Liquid
Viscosity @ 40°C	Density @15.6	Flash point	pH

APPLICATION

- Total-loss oilers and drip feed lubrication
- Plain bearings and pillow blocks
- Textile machinery general lubrication
- Chains, slides and open lubrication points

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL1

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Physical form		**Liquid**
Colour ASTM D1500		**Amber**
Odour		**Oily**
Boiling Point (Typical)	°C	**> 230**
Viscosity @ 40°C	cSt	**135 – 165**
Flashpoint °C (C.C)		**223**
Density @15.6	°C	**0.891**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963