INDUSTRIAL OILS · HYDRAULIC OILS

SARMAX FILTRO HYDRAULIC OILS – ISO 46.

The standard SARMAX hydraulic oil taken a stage further: after blending, every batch is filtered to a far tighter cleanliness code than a normal industrial fill.

46 cSt	6.3 cSt	0.877	210 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Commissioning fills on new machine tools
- Servo and proportional valve hydraulics
- Systems with a written ISO 4406 cleanliness target
- Top-ups that must not raise the particle count

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 8 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51524 Part 2 (HLP)
Denison	HF-2, HF-1, HF-0, Filterability TP 02100
Sperry	Vickers 1-286-SC
Cincinnati	Milacron P-68, P-70
AFNOR	NF E 48-603 (HM)
FZG	Damaging Stage 12
US	Steel 126 / 127 For R & O Hydraulic Fluids

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
ISO Viscosity @ 40°C		**46**
ISO Viscosity @ 100°C		**6.3**
Density @ 15°C ASTM D4052		**0.877**
Pour Point	°C	**-24**
Flash Point (COC)	°C	**210**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963