INDUSTRIAL OILS · HYDRAULIC OILS

SARMAX HFC 46.

A fire-resistant HFC hydraulic fluid: polyalkylene glycols dissolved in a stable water solution, so roughly 44% of what is in the tank is water.

APPLICATION

- Die casting and forging press hydraulics
- Furnace door and charging gear
- Any hydraulic circuit with a credible ignition source nearby
- Applications where an HFC fluid is written into the insurer's requirements

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Pink coloured liquid**
ISO Grade		**46**
Viscosity @ 40 °C		**43.0 – 49.0**
Viscosity Index ASTM D2270		**> 200**
Water Content ASTM D6304	%	**44**
IP 135 Rust Test (Part 1)		**No rust**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963