INDUSTRIAL OILS · HYDRAULIC OILS

# SARMAX HFDU HYDRAULIC 68.

A fire-resistant HFDU fluid based on synthetic esters, which does something a water-glycol cannot: it is fire resistant and fully biodegradable and behaves much more like a conventional oil in the pump.

| 65 cSt | 0.928 | 290 °C | -32 °C |
|---|---|---|---|
| Viscosity @ 40°C | Density @ 20°C g/cm³ | Flash point | Pour point |

## APPLICATION

- Fire risk areas that also need environmental cover
- Dockside cranes and lock gear
- Hydro and water-industry hydraulics
- Tunnelling and underground plant

### NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 4 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **FM** | approved formulation |
| **ISO** | 15380:2016 (international standard for environmentally acceptable hydraulic fluids), 6743-4:2015 (rapidly-biodegradable hydraulic fluids, HEES class) |
| **VDMA** | 24568 (environmentally-friendly hydraulic fluids based on synthetic esters, HEES class) |

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963

INDUSTRIAL OILS · HYDRAULIC OILS · CONTINUED

# SARMAX HFDU HYDRAULIC 68.

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Yellow – Brownish** |
| Density @ 20°C | g/cm$^3$ | **0.928** |
| Viscosity @ 20°C | mm$^2$/s | **158** |
| Viscosity @ 40°C | mm$^2$/s | **65** |
| Viscosity @ 50°C | mm$^2$/s | **45** |
| Viscosity Index<br>ASTM D2270 | | **185** |
| Flash Point | °C | **290** |
| Fire Point | °C | **375** |
| Pour Point | °C | **-32** |
| Auto Ignition Temp | °C | **490** |

Typical values, not a specification.

**PACK SIZES**

20 L, 205 L, 1000 L IBC, Bulk

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963