INDUSTRIAL OILS · HYDRAULIC OILS

SARMAX HYDRAULIC OILS VHVI 100.

A very high viscosity index hydraulic oil, built by combining refined mineral base oil with a shear-stable viscosity index improver and a full HVLP additive system.

100 cSt	14.0 cSt	0.875	220 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Excavators, loaders and mobile plant working outdoors
- Systems that must start cold and run hot in the same shift
- Hydrostatic transmissions and travel motors
- Sites replacing a seasonal summer/winter grade change with one fill

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
ISO Viscosity @ 40°C		**100**
ISO Viscosity @ 100°C		**14.0**
Density @ 15°C ASTM D4052		**0.875**
Viscosity Index (Typical)		**142**
Flash Point (COC)	°C	**220**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 11 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51524 Part 2 and 3 (HVLP)
ISO	11158 (HV)
ASTM	D6158 (HV)
Fives-Cincinnati	P-68 (ISO 32 – HV), P-69 (ISO 68 – HV), P-70 (ISO 46 – HV)
Parker-Denison	HF-2, HF-1, HF-0 (HV) (ISO 32, 46, 68)
Sperry-Vickers	35 VQ25
Eaton	E-FDGN-TB002-EGB 11118.1-2011 (L-HV, L-HS) (ISO 15, 22, 32, 46)
AIST	126, 127 (ISO 32, 46, 68)
SEB	181222 (ISO 22, 32, 46, 68 and 100)

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963