INDUSTRIAL OILS · HYDRAULIC OILS

SARMAX HYDROL DETERGENT HYDRAULIC OILS – ISO 46.

A detergent-dispersant hydraulic oil - HLP-D rather than plain HLP.

46 cSt	210 °C	-24 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Mobile plant hydraulics exposed to weather
- Marine and dockside systems
- Older equipment with known water ingress
- Combined hydraulic and wet-brake circuits

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51524 Part 2 (HLP-D)
ASTM	D6158 (HM)
ISO	6743-4 (HM)

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
ISO Viscosity @ 40°C		**46**
Pour Point	°C	**-24**
Flash Point (COC)	°C	**210**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963