INDUSTRIAL OILS · HYDRAULIC OILS

SARMAX ZF HYDRAULIC OILS – ISO 100.

A zinc-free, ashless hydraulic oil on low-sulphur base stocks.

100 cSt	10.8 cSt	0.889	225 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Systems containing bronze, brass or silver-plated parts
- Hydraulics running with persistent water ingress
- Sites minimising heavy metals in their effluent
- Power generation and water industry hydraulics

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
ISO Viscosity @ 40°C		**100**
ISO Viscosity @ 100°C		**10.8**
Density @ 15°C ASTM D4052		**0.889**
Pour Point	°C	**-18**
Flash Point (COC)	°C	**225**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 10 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51524 Part 2 (HLP)
Parker	(Denison) HF-2, HF-1, HF-0
Eaton	Vickers I-286-S
Fives	(Cincinnati) P-68, P-69, P-70
Bosch Rexroth	RE 90 220
AFNOR	NF E 48-603 (HM)
ASTM	D6158 (HM)
SAE	MS 1004 (HM)
ISO	11158 (HM), 20763 vane pump test

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963