TEXTILE LUBRICANTS · MACHINE LUBRICANTS

SAROL 100E.

SAROL 100E is a general purpose textile machine lubricant manufactured from a blend of solvent-refined mineral oils and non-ionic emulsifiers, used where scourability is required.

APPLICATION

- General purpose textile machinery lubricant where scourability is required

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour & Appearance		**Pale Amber liquid**
Density @ 15.6°C		**0.898 kg/m3**
Cloud Point	°C	**>70**
Kinematic Viscosity @ 40°C	cSt	**90 – 110**
Solubility in water		**Emulsifies readily**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963