METALWORKING FLUIDS · SOLUBLE CUTTING FLUIDS

SARSOL 102 W.

SARSOL 102 W is the latest in boron and formaldehyde free technology for general purpose machining, forming and roll forming applications, featuring high levels of synthetic ester lubricity, inherently low foam, and suit

APPLICATION

- general machining
- metal forming
- roll forming
- galvanised steel
- zinc coated materials
- yellow metals

NOT RECOMMENDED

- × **Machining of magnesium, or of aluminium where a low-pH fluid is required**
- × **Use as a hydraulic or slideway oil - cross-contamination will shorten sump life**

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind - free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance (Concentrate)		**Amber liquid**
Appearance (Emulsion)		**Milky**
pH (4% emulsion)		**9.2–9.4**
IP 287 Breakpoint	%	**4.0**
Mineral Oil Content		**High**
Refractometer Conversion Factor		**1.0**
Make Up Water Hardness	ppm	**50–250**
Light Duty	%	**5.0%–6.0**
Medium Duty	%	**7.0%–8.0**
Heavy Duty	%	**8.0%–10.0**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963