TEXTILE LUBRICANTS · ANTI-STATIC AGENTS

SARSTAT C.

SARSTAT C is an anti-static agent that can be employed at various stages of fibre/yarn processing and has proved to be very effective on most textile fibres including synthetic fibres such as acrylic and nylon.

APPLICATION

- fibre/yarn processing
- gilling
- static dissipation on acrylic and nylon fibres
- spray application
- roller application

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear, water-white liquid**
Ionic Character		**Cationic**
Density		**1.0**
Solubility		**Mixes readily with water**
Biodegradability OECD 301B		**Expected to be biodegradable**

Typical values, not a specification.

PACK SIZES

25 Kilo Kegs, 200 Kilo Drums, 1000 Kilo IBC's

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963