METALWORKING FLUIDS · ANTI-CORROSION PRODUCTS

# SARTEC 10.

SARTEC 10 is a low viscosity rust preventative and water displacement fluid, which leaves a thin protective film.

| 0.811 | 64 °C | Amber |
|---|---|---|
| Specific Gravity @ 15.6 | Flash point | Colour |

## APPLICATION

- Short term protection of metal components stored undercover
- water displacement

**NOT RECOMMENDED**

- × **Machining of magnesium, or of aluminium where a low-pH fluid is required**
- × **Use as a hydraulic or slideway oil - cross-contamination will shorten sump life**

## BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind - free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Fluid Oil** |
| Colour<br>ASTM D1500 | | **Amber** |
| Specific Gravity @ 15.6°C | | **0.811** |
| Flash Point<br>ASTM D92 | °C | **64** |
| Indoor Protection | | **3 Months** |
| Outdoor Protection Covered | | **Not Recommended** |
| Outdoor Protection Uncovered | | **Not Recommended** |

Typical values, not a specification.

**PACK SIZES**

25 L, 205 L, 1000 L IBC

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963