INDUSTRIAL OILS · HEAT TRANSFER OILS

# SARTHERM AO SYN 32.

A synthetic heat transfer fluid on Group III hydrocracked base stock, for closed and low temperature open thermal fluid systems.

| 35 cSt | 6 cSt | 240 °C | -30 °C |
|---|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Flash point | Pour point |

## APPLICATION

- Closed-loop thermal fluid heating systems
- Process heating on textile stenters and dryers
- Jacketed vessels and calenders
- Low temperature open thermal systems

### NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Clear, bright colourless liquid** |
| Viscosity @ 40°C | cSt | **35** |
| Viscosity @ 100°C<br>ASTM D445 | cSt | **6** |
| Pour Point<br>ASTM D97 | °C | **-30** |
| Flashpoint (COC) | °C | **240** |
| Evaporate Loss, NOACK | % | **9.0** |
| Nitrogen | ppm | **<1** |
| Sulphur | ppm | **<1** |

Typical values, not a specification.

### PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963