OFF-HIGHWAY & AGRICULTURE · SUPER UNIVERSAL TRACTOR OILS

SARTRAC STOU 15W-30.

The value grade in the STOU range, built to an earlier but still widely specified performance level - API CE/SF and ACEA E2 rather than CG-4 and E3.

APPLICATION

- Older tractors specified to API CE/SF
- Contractors running mixed-age fleets
- Cost-sensitive general farm use
- Machines that gain nothing from a CG-4 oil

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 9 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CE / SF, GL-4
ACEA	E2
Ford	M2C-159B
Massey Ferguson	M1135, M1139
Allison	C3
John Deere	J20A, J20B, J27
CAT	TO-2
ZF	TE-ML 06A

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Kinematic Viscosity @ 100°C	cSt	**12.5**
Specific Gravity @ 15.6°C		**0.890**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963