OFF-HIGHWAY & AGRICULTURE · AGRICULTURAL SPECIALITIES

SHIRE OIL.

A very light, highly refined, water-white oil used on shire horse feathers to improve condition and appearance.

20.8 cSt	0.841	210 °C
Viscosity @ 40°C	Specific Gravity @ 15	Flash point

APPLICATION

- Conditioning shire and heavy horse feathers
- Showing and turnout preparation
- Stable and yard use

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear, water white liquid**
Kinematic Viscosity @ 40°C	cSt	**20.8**
Specific Gravity @ 15°C		**0.841**
Flashpoint °C (CC)		**210**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963