AUTOMOTIVE · MANUAL TRANSMISSION FLUIDS

MULTIVEHICLE MTF 75W80 GL-4+.

A fuel-efficient, manual transmission fluid formulated with the very latest additive technology to offer high levels of gear protection and synchronizer compatibility.

50.9 cSt	8.9 cSt	0.855
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6

APPLICATION

- Modern passenger car manual transmissions where gearbox and differential share the same unit

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 35 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4
	GL-4+
BMW	MTF LT-2
GM	1940004, 1959104, 1940764, 1940768, 1940182, W16612 (dry DCT)
FIAT	MZ1, MZ6
FORD	M2C 186-A, M2C 200-C, M2C 200-D2 (dry DCT)
Honda	Special MTF, MTF-II, MTF-III
Nissan	MT-X, MT-XZ TL (JR Type)
PSA	B71 2330 (EZL 848), B71 2315, B71 2316 (HBVFE)
Renault	DC4 DWS (dry DCT)
Volvo	97308, 97309
VW	G 052 512 (dry DCT), G 055 512 (dry DCT), G 052 171, G 052 178, G 052 726, G 060 726, G 50, G 009 317, G 052 527 A2, G 070 726 A2

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

AUTOMOTIVE · MANUAL TRANSMISSION FLUIDS · CONTINUED

MULTIVEHICLE MTF 75W80 GL-4+.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 15.6°C		**0.855**
Viscosity @ 100°C ASTM D445	cSt	**8.9**
Viscosity @ 40°C	cSt	**50.9**
Viscosity Index ASTM D2270		**156**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963