TEXTILE LUBRICANTS · KNITTING OILS

PERFAKNIT 32.

PERFAKNIT 32 is a highly efficient needle lubricant possessing good emulsion-forming properties with excellent antiwear performance, blended with high-quality hydroprocessed base oils.

APPLICATION

- Lubrication of needles
- Sinkers and cams of all types of knitting machines including electronic machines
- Flat-bed machines

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Does	not contain substances banned by GOTS
ZDHC	compliant
Oeko-Tex	Standard 100
Bluesign	compliant

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Bright and clear**
Colour ASTM D1500		**Colourless to pale yellow**
Kinematic Viscosity @ 40 °C	cSt	**32.1**
Density @ 15 °C ASTM D4052		**0.870**

Typical values, not a specification.

PACK SIZES

25 L | 205 L | 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963