TEXTILE LUBRICANTS · FIBRE & YARN LUBRICANTS

PERFALUBE MHL.

PERFALUBE MHL is a highly anti-static, readily scourable, woollen spinning lubricant designed for hosiery yarn production on the woollen system, comprising a blend of non-ionic surfactants, fatty materials and solvent re

33 cSt	>200 °C	5-6	4-8
Viscosity @ 40°C	Flash point	pH	Colour

APPLICATION

- woollen spinning
- hosiery yarn production
- Shetland (8-11%)
- Lambs Wool (5-7%)
- Cashmere (4-5%)
- Lambs Wool/Angora/Nylon (3-4%)

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Does	not contain banned substances listed by GOTS/ZDHC
Oeko-Tex	Standard 100 and Bluesign

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Pale yellow liquid**
Colour (Gardner 10mm cell)		**4-8**
Viscosity @ 40°C	cSt	**33**
Flash Point (COC)	°C	**>200**
Ionic Activity		**Non-ionic**
Specific Gravity @ 15°C		**0.890-0.950**
pH of emulsion (at 25%)		**5-6**

Typical values, not a specification.

PACK SIZES

205 ltr drums, 1000 ltr IBC's, bulk deliveries. Other pack sizes and bulk deliveries up to 25,000 litres available on request

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963