TEXTILE LUBRICANTS · FIBRE & YARN LUBRICANTS

PERFASCOUR LAN.

PERFASCOUR LAN is a single addition scouring agent for wool and cashmere knitwear, developed for processing knitted garments manufactured in natural fibres, containing non-ionic and anionic detergents and blended buffers

APPLICATION

- scouring of wool and cashmere knitwear
- knitted garments in natural fibres
- optimum scouring temperature 40-45°C
- normal application levels 5-10% owf

NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Does	not contain banned substances listed by GOTS/ZDHC
Oeko-Tex	Standard 100 and Bluesign

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Clear colourless liquid**
Ionic Activity		**Non-ionic/Anionic**
Specific Gravity @ 15°C		**1.050-1.100**
pH (1% aqueous solution)		**7.0-9.0**

Typical values, not a specification.

PACK SIZES

120 & 200 kg drums, 1000 kg IBCs, bulk deliveries

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963